

Technical Data Sheet



Nirumand Polymer Co.
Filled & Reinforced Engineering Plastics

NIRUCALCIT-LD20

Low Density Polyethylene Filled with Calcium Carbonate

Nirumand Polymer

Product Description

NIRUCALCIT-LD20 is low density polyethylene filled with calcium carbonate. This grade features excellent filler dispersion in polymer resin, good tear resistance and flexibility of produced film. This compound is used in film blowing process. Moreover, it results in improving productivity and decreasing product costs.

General Properties

Material Status	•Commercial: Active
Forms	•Pellets
Processing Method	•Film blowing
Color	•White

Properties	Value	Unit	Test Method
Density	1.9	gr/cm ³	ISO 1183
Dispersion	Excellent	...	Internal Method
Moisture	≤ 0.2	%	ASTM D570

Special Characteristics

Appropriate miscibility with base resin

The excellent dispersion of filler in the matrix

Improve printability

Increase of productivity

Decrease finished product cost

Increase tear resistance and flexibility of produced film

White pigment saving

◆ Values shown are average & are not to be considered as product specifications.

Web-site: www.npolymer.com

Address: Abbas abad Industrial Zone-Tehran-Iran

E-mail: Sales@npolymer.com

Tel: (+9821)35000234 Fax: (+9821)43850755