

Technical Data Sheet

ABS-I1R-3

Acrylonitrile - Butadiene - Styrene

Nirumand Polymer



Nirumand Polymer Co.
Filled & Reinforced Engineering Plastics

Product Description

ABS-I1R-3 is a recycled thermoplastic with good mechanical properties. This grade is used for a wide range of applications including auto parts, home appliances, electrical parts/fittings, telecommunication and electronic devices. This grade is designed to be used in conventional injection molding process.

General Properties

Material Status	•Commercial: Active
Forms	•Pellets
Processing Method	•Injection
Color	•Black

Physical Properties	Value	Unit	Test Method
Melt Mass-flow Rate (MFR) (220°C/10 Kg)	18	gr/10 min	ASTM D1238
Shrinkage	%	Internal

Mechanical Properties	Value	Unit	Test Method
Tensile Strength@Yield	40	MPa	ISO 527
Elongation @ Break	...	%	ISO 527
Flexural Modulus	1900	MPa	ASTM D790

Impact	Value	Unit	Test Method
Notched Izod Impact (23°C)	3	kJ/m ²	ISO 180
Notched charpy Impact (23°C)	kJ/m ²	ISO 179

Hardness	Value	Unit	Test Method
Durometer Hardness	...	Shore D	ASTM D2240

◆ Values shown are average & are not to be considered as product specifications.

Web-site: www.npolymer.com

Address: Abbas abad Industrial Zone-Tehran-Iran

E-mail: Sales@npolymer.com, Trade@npolymer.com

Tel & Fax: (+9821)35000234